



DR1900 Portable Spectrophotometer

The DR1900 excels in the field because it is the lightest and most compact portable spectrophotometer. Your field testing takes you to potentially dusty and wet conditions where other equipment simply won't be safe. The instrument is built for rugged conditions, and it's flexible, accepting the widest range of vial sizes. Built with field use in mind, the DR1900 has a large, clear screen and a simple user interface that makes testing easier than ever in even the most demanding conditions. Easy to hold, and operate, the compact DR1900 is a valuable tool for your field technicians.

Underneath the rugged exterior, the spectrophotometer has the largest number - over 220 - of the most commonly tested preprogrammed methods already built in. You can also use the easy-to-use interface to create your own methods. Tests are performed with a wavelength range of 340 to 800 nm which make this a field instrument you can use to find results typically only seen in laboratory instruments.

Please note: LCK cuvette test evaluation is possible, but without barcode identification & 10 fold measurement and outlier elimination.

- Test what you need
- Ensure accuracy in the field
- Make testing easier

Part Number	Name	Interface	Wavelength Range	Power supply	Web Price
DR1900-01H	DR1900 Portable Spectrophotometer	USB type Mini IP67 (with optional Module)	340 - 800 nm	4 x AA size Alkaline 4x NiMH rechargeable Battery* Power supply*: 110 - 240 V; 50/60 Hz (* optional Module required. May not be available in all regions)	Contact Hach
9624700	DR1900 Portable Spectrophotometer with USB + Power Module	USB type Mini IP67 (with optional Module)	340 - 800 nm	4 x AA size Alkaline 4x NiMH rechargeable Battery* Power supply*: 110 - 240 V; 50/60 Hz (* optional Module required. May not be available in all regions)	Contact Hach

Part Number	Name	Interface	Wavelength Range	Power supply	Web Price
DR1900-02L	DR1900 Portable Spectrophotometer	USB type Mini IP67 (with optional Module)	340 - 800 nm	4 x AA size Alkaline 4x NiMH rechargeable Battery* Power supply*: 110 - 240 V; 50/60 Hz (* optional Module required. May not be available in all regions)	Contact Hach